## I. Overview

**SX-06L is a high quality USB hand phone with LCD and 4-polyphonic ring tones. The fully functional keypad and the LCD screen enable you to make/receive Skype calls without using mouse and keyboard. Just plug it into your PC or laptop, and then you can enjoy the full features of Skype™.**

## II. The Phone Layout

## III. Host System Requirements

- ü Microsoft Windows 2000/XP
- ü Pentium 400MHz above processor/128MB RAM/16MB free hard disk capacity.
- ü One USB port available.
- ü Internet connection (ADSL, Cable Modem, Dial-Up, Wireless LAN)

## IV. Key Features

**Here below are the key features of the USB Phone SX-06L:**

- **Monochrome 128*64 pixel LCD. Supports all kinds of languages**
- **Skype Contact List, Call List and time display on LCD screen**
- **12 classical 4-polyphonic ring tones catering to different tastes.**
- **Rings loudly on an incoming call.**
- **Fully functional keypad and LCD screen enables you to make/receive calls without using keyboard and mouse.**
- **Power LED and Status LED.**
- **Mic. mute button to protect your privacy.**
- **Supplied earphone for hands-free operation.**
- **Acoustically isolated earpiece and microphone to eliminate echo.**
- **Full-duplex communication with crystal clear sound.**
- **USB interface PnP. No external power/sound card needed.**
- **Also compatible with many other PC-based softphone applications, such as MSN, Yahoo Message, Xten, Dialpad, MediaRing, Net2phone, etc.**

## V. Specifications

| | | |
|---|---|---|
| **Weight** | **90g** | |
| **Dimension** | **48*120*24mm** | |
| **USB Port** | **Mini USB A-type** | |
| **Earphone Connector** | **2.5mm** | |
| **Standard Support** | **Compliant with USB V 1.1**<br>**Compliant with USB Audio Device Class Spec V 1.0**<br>**Compliant with USB HID Version 1.1** | |
| **LED** | **Power LED** | **Red** |
| | **Status LED** | **Green** |
| **LCD** | **Size** | **29mm*13.5mm** |
| | **Pixel** | **128*64** |
| **Voltage** | **4~5.25 V** | |
| **Operating Humidity** | **5~95%RH** | |
| **Operating Temperature** | **0~40℃** | |

## VI. Ordering Information

| Model | Description |
|---|---|
| **SX-06L** | **Private label available** |